



**Technical Data**

Supply voltage	5 V DC ± 500mV
Average power consumption	72 mA
Ambient temperature during operation	0 °C to +40 °C
Cable length	2070 mm ± 50mm
Dimensions (l x w x h)	119.0mm x 129.0mm x 9.6mm
Degree of protection	IP20
Compatible motor control boxes	S1 (firmware version 1.8 or higher)

This drawing don't subject to the revision service.														
Without our specifically acceptance, this drawing is not allowed to be copied or given to other persons.	scale: drawing not in scale	position:												
<table border="1"> <thead> <tr> <th></th> <th>date</th> <th>name</th> </tr> </thead> <tbody> <tr> <td>edited</td> <td>22.08.2018</td> <td>V.Skeljic</td> </tr> <tr> <td>check.</td> <td>19.09.2018</td> <td>S.Lägeler</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> </tbody> </table>		date	name	edited	22.08.2018	V.Skeljic	check.	19.09.2018	S.Lägeler				Handswitch with integrated display shift mechanism and 2 Motorgroups four memorie positions + Up/Down	
	date	name												
edited	22.08.2018	V.Skeljic												
check.	19.09.2018	S.Lägeler												
Bansbach easylift GmbH Barbarossastr. 8 D-73547 Lorch/Württemberg		sheet												