

| LOCK WITH METAL BUTTERFLY HANDLE | | | | | |
|---------------------------------------|------------------|---------------|------------------|---------------------|---------|
| GH VALUE | CATALOGUE NUMBER | | | MATERIAL AND FINISH | |
| | Cylinder 1333 | Cylinder - RK | Without cylinder | Handle | Housing |
| GH=18 T _{sm} ax-8 | 2.PM18.002 | 2.PM18.004 | 2.PM18.006 | ZAMAK | |
| | 2.PM18.001 | 2.PM18.003 | 2.PM18.005 | RAL9005 | |
| GH=30 T _{sm} ax-18 | 2.PM30.002 | 2.PM30.004 | 2.PM30.006 | Chrom | |
| | 2.PM30.001 | 2.PM30.003 | 2.PM30.005 | RAL9005 | |
| GH=40 T _{sm} ax-28 | 2.PM40.002 | 2.PM40.004 | 2.PM40.006 | Chrom | |
| | 2.PM40.001 | 2.PM40.003 | 2.PM40.005 | RAL9005 | |
| GH=60 T _{sm} ax-48 | 2.PM60.002 | 2.PM60.004 | 2.PM60.006 | Chrom | |
| | 2.PM60.001 | 2.PM60.003 | 2.PM60.005 | RAL9005 | |


| LOCK WITH POLYAMIDE BUTTERFLY HANDLE | | | | | |
|---------------------------------------|------------------|---------------|------------------|------------|---------|
| GH VALUE | CATALOGUE NUMBER | | | FINISH [C] | |
| | Cylinder 1333 | Cylinder - RK | Without cylinder | Handle | Housing |
| GH=18 T _{sm} ax-8 | 2.PMPA18.002 | 2.PMPA18.004 | 2.PMPA18.006 | Poliamid* | ZAMAK |
| | 2.PMPA18.001 | 2.PMPA18.003 | 2.PMPA18.005 | | RAL9005 |
| GH=30 T _{sm} ax-18 | 2.PMPA30.002 | 2.PMPA30.004 | 2.PMPA30.006 | RAL9005 | Chrome |
| | 2.PMPA30.001 | 2.PMPA30.003 | 2.PMPA30.005 | | RAL9005 |
| GH=40 T _{sm} ax-28 | 2.PMPA40.002 | 2.PMPA40.004 | 2.PMPA40.006 | | Chrome |
| | 2.PMPA40.001 | 2.PMPA40.003 | 2.PMPA40.005 | | RAL9005 |
| GH=60 T _{sm} ax-48 | 2.PMPA60.002 | 2.PMPA60.004 | 2.PMPA60.006 | | Chrome |
| | 2.PMPA60.001 | 2.PMPA60.003 | 2.PMPA60.005 | | RAL9005 |

| METAL LOCK WITH BUTTERFLY HANDLE WITH SHAPED INSERT | | | | | |
|---|-------------------|------------------|---------------------|---------|--------|
| GH VALUE | CATALOGUE NUMBER | | MATERIAL AND FINISH | | |
| | Shape insert KW8 | Shape insert T8 | Handle | Housing | Insert |
| GH=18 T _{sm} ax-8 | 2.PM18-KW8 | 2.PM18-T8 | ZAMAK | | Steel |
| | | | RAL9005 | | |

How to order:

Catalogue number

Type of cam



where:

H.G:**H** - height locking**G** - cams range

Ts - Thickness door

Lock is compatible with all cams from range: 11, 12, 13, 14, 18, 31, 32, 34, 38, JK-1610.01

Each lock with a cylinder is supplied with two keys.

* The 2.PMPA lock handle is a two-component, injection-moulded plastic on an internal element made of metal (ZAMAK).

Lock with a butterfly handle and shaped insert. 2.PM18-KW8(T8) allows emergency opening by means of a handle.

The KW8 or T8 key is used to open the standard butterfly lock, which can be operated as a standard.